

# CURBSTONES MARKING PAINT

▶ <b>Product code No.</b>	Black 448-952
▶ <b>Product Description</b>	Paint for marking curbstones. Based on alkyd resins. Fast drying,
▶ <b>Special Features</b>	Free of lead, chromates and/or any other toxic pigment.
▶ <b>Suggested uses</b>	Designed for curbstones made from concrete. marking parking lots, floors of warehouses, halls, etc. Not for use on asphalt roads.
<b>Technical data</b>	
▶ <b>Color</b>	Black
▶ <b>Gloss at 60°C</b>	Matt.
▶ <b>Solid content by volume</b>	45-50%
<b>Viscosity</b>	80-85 K.U
▶ <b>Calculated spreading rate* (liter/sq.m)</b>	0.4 – 0.7 liter (see details below).
▶	
<b>Touch dry**</b>	15 minutes.
▶ <b>Open time for traffic</b>	20-30 minutes.
<b>Storage</b>	
▶ <b>Shelf life**</b>	12 months.

**Surface preparation and specification** Clean curbstones surface from dust, grease and any other foreign matter. Do not paint on a wet or damp surface, when rain is expected or in extreme weather conditions. The required amount according is 0.4 liters per square meter. Over rough aggregate (larger than 2 mm), or when small holes must be filled, use higher amounts of paint, up to 0.7 liter per one square meter. Use such higher amounts of paint for application on seams or patches. The preparation of asphalt roads for marking by paint is according EN 1436-2004 and EN 13036-4-2003 (or 934/1 of Israel Institute of standardization).

► **Paint application** Method  
 Brush/roller  
 1-22  
 0-5%  
  
 Airless spray  
 4-5  
 0.018 -0.021”  
 1-22  
 0-5%

► **Cleaning Thinner** Thinner for road marking paint (or thinner 1-22).

**Application remarks** Stir well before application and while painting.  
**Warning:** Excessive brushing may melt the road asphalt and cause color changes in the paint (bleeding).

**Caution** Any work that includes application and use of this product shall be performed according to the applicable Safety, Health and Environmental regulations. Read the safety precautions and the warnings specified in the Safety Data Sheet, available at Tambour Safety Department and indicated on the product's label.  
 Keep away from fire and sparks. Inedible. Provide adequate ventilation of the work space. Use appropriate protective means, as indicated in the Safety Data Sheet.  
 Do not inhale fumes when spraying this product.

**Warning** Never mix this material with others when not specifically recommended by us.

**General comments** Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

\* Practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.  
 \*\* At 25°C and 65% relative humidity.