

Glow in the Dark

Water-based acrylic paint for interior walls, wood and metal that glows in the dark in a green-blue shade.

Technical data:

Product code:	795-510
Shade in day light:	Yellow-Green
Shade in dark:	Green- Blue
Gloss:	Matt
Calculated coverage:	1 m2/l
Thinning:	Water
Cleaning:	Soap and water
Drying time:	about 15 mn
Shelf life:	24 month
Package Size:	0.25 l.

Paint characteristics:

The paint charges itself with exposure to day light and glow in the dark for 2 to 8 hours.

Paint use:

Water-based acrylic paint for interior walls, ceilings, wood or metal to be used over acrylic painted walls.

General Guidelines:

Apply two coats of acrylic paints on a chosen surface. Wait for complete drying (3 hours). It is recommended to apply Glow in the Dark on light colors. The lightest the background color, the stronger the effect will be.

Application:

It is recommended to paint with a pattern. Tape the pattern to the surface you wish to adorn. Dip the tip of the provided brush in a little paint. Fill the pattern with a thick coat by tapping with the brush tip. After filling the pattern, remove carefully and clean immediately.

After application:

After the paint has dried, expose it to a light source (daylight, neon, halogen, ordinary lamp) for at least 8 hours. The stronger the light source, the shorter the charging time will be and in result the duration of the glow will last longer. The thicker the coat of paint is applied the higher its glow capacity will be.

In the future if you would like to paint over the Glow in the Dark paint, lightly sand the paint off the wall, clean and then apply two coats of acrylic paint.

Drying Time: for contact – 15 minutes

Tools cleaning and storage:

Clean the tools and pattern with water and soap immediately after the work is done. Firmly seal the packaging to prevent air infiltration. Store in a closed and properly ventilated space.

Warnings and precautions:

Safety Measures: Inedible. This paint is not defined as a hazardous material and does not contain materials requiring special marks or warnings. Safety data sheets for professional users are available upon request.

General Remarks: Do not apply the paint when rain is expected or when ambient temperature falls below 10°C and relative humidity exceeds 85%. Never mix this material with others when not specifically recommended by us. The desired results are obtained only through correct application of the product according to the application instructions. The user must ensure, prior to application, that the recommended products are suitable to his requirements, method of application and environmental conditions and that the surface and its substrate are prepared properly. Data presented here is based on our best knowledge and experience. We reserve the right to update or alter without prior notice.