

HAMMERTON THINNER

A special thinner for the HAMMERTON series of paints

SUGGESTED USES

Dilution of HAMMERTON series paints.

TECHNICAL DATA

Product code:	654-900	
Color:	Transparent	
Shelf life:	24 months	
Quantity per Pallet:	Package size	Quantity per Pallet
	0.50 liter	900

APPLICATION REMARKS

Thinner ready for use.

CLEANING AND STORAGE

Close the container tightly to avoid entry of air. Store in a cool, well-ventilated place..

CAUTION

Application and use of this product should be according to the safety, hygiene and environmental regulations of the State of Israel. Read the safety instructions and warnings in the Product Safety Sheet (MSDS), which may be obtained from our Safety Dept. on request. Telephone: 04-9877483 – and also on the product labels. Keep well away from fire and sparks. The material is not edible. Make sure the workplace is well ventilated. When spraying, avoid inhaling the vapors.

GENERAL COMMENTS

Do not paint if rain is expected within the next 72 hours, and/or if the temperature is below 10°C and Relative Humidity (R.H.) is above 85% When painting on wood or metal substrates, make sure that the substrate is perfectly dry. Do not mix this material with other materials not recommended by us. To attain the best desired results, the product must be applied correctly, paying careful attention to instructions. Before use, the user should make certain that the correct material has been selected for the purpose intended, and that the surface to be painted, and the under-surface, have been properly prepared for the application selected. The information provided here is based on many years' accumulated knowledge and experience. We reserve the right to update or to alter it without prior notice
Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

HAMERTON WATER BASED

A high-grade acrylic paint, for dilution with water, giving a smooth finish both as primer and as topcoat, with strong binding power to a variety of substrates, with excellent resistance to outside conditions, giving protection against corrosion to metal surfaces.

PROPERTIES:

Has strong adhesion to various undersurfaces, such as: Ferrous metals, aluminum, hot and cold galvanized iron, ceramics and Formica. Specially fast drying. Contains no lead or chromates. Carries "Green" label. Ready to use. Environment- and user-friendly

APPLICATIONS:

Very high binding power, to a variety of substrates. Protects metal and galvanized surfaces (railings, bars, etc.) from rust and weathering

TECHNICAL DATA:

Product code: 764-XXX

Color: White and four smooth satin basic shades in TAMOURMIX for obtaining 1200 shades of the spectrum chart and RAL chart.

Gloss: Smooth satin.

Type of paint: Primer + topcoat **based on:** High-grade pure acrylic emulsion

% solids v/v 35%+/-2%

Thickness of single-layer dry film: 40 – 60 microns

Calculated spreading rate*: 11-13 sq.m/liter (in one coat)

Dilution: Water

Drying Times: **Touch dry**:** 30 minutes; **Hard Coat:** 24 hours **Dry to recoat:** You can recoat after 2 hours.

Shelf life: 24 months

Quantity per Pallet:	Package size	Quantity per Pallet
	4.5 Liters	100
	0.75 Liters	576

SURFACE PREPARATION AND PAINT SYSTEM:

Ferrous metals:

Before commencing painting, make sure the surface to be painted is clean and dry. Remove all oily materials, using a thinner such as: **Tambour Mineral Turpentine**. Remove dirt, rust, metal scale and any other foreign matter, using a steel wire brush and emery paper. Afterward, wash with water. Apply 2 – 3 coats of **Water Based Hamerton** at intervals of 2 hours between coats.

* In cases where rust can not be mechanically removed as described above, rust may be neutralized with **Tambour Rust Converter**. Afterward, apply 2 – 3 coats of **Water Based Hamerton** and allow to dry completely.

Galvanized iron and aluminum.

