

NEGBA - Sandy mineral looking paint

Water-based paint with a mineral look, sandy texture and a cloudy appearance.

PROPERTIES

Water-based paint that is easy to apply and can give a natural sandy look to indoor and outdoor walls.

SUGGESTED USES

Suitable for a single wall design or for several walls to create a prominent look. An appearance well recognized with historic buildings (Tuscan or Provence style). Adds a natural look to the house's design. Easy to apply and designed for both amateurs and professionals.

TECHNICAL DATA

Product code: 739-740

Color: 1200 colors from color fan colors

Gloss: Matte

Texture: Sandy

Calculated spreading rate (liter/m²): 6-8 m² two layers

Dilution: Ready to use (may be diluted with water up to 15% if necessary).

Drying times: Touch dry 1-2, Hard dry: 72 hours, weather dependent

Time between layers: 2 hours or more

Shelf life: 6 months.

SURFACE PREPARATION AND PAINT SYSTEM

Outdoor walls:

Before applying remove every loose or peeling layer. Make all the necessary concrete and plaster repairs with outdoor suitable materials. **Paint 2 layers of binding primer diluted with 30% turpentine when the infrastructure is very old or coating primer (737500) diluted with 20% water on strong infrastructures.** Apply a layer of "NEGBA" using a brush in two layers or in a Tuscan coating style using a metal putty knife. After 10 minutes of waiting press with a plastic putty knife.

Indoor walls:

- Proper acrylic-painted walls: remove dust and apply two layers of "NEGBA"
- Plaster walls: Apply a basic layer and two layers of "NEGBA"
- Whitewash painted walls or walls with old peeling acrylic paint: Apply a basic layer and two layers of "NEGBA"

APPLICATION REMARKS

Apply with a brush without diluting in two layers. Apply the first layer normally and the second layer in an "X" maneuver.

CLEANING AND STORAGE

Clean the tools with soap and water immediately after completing the work. Pour a thin layer of water on any remaining paint and close container well so that it is airtight. Store in a dark, well-ventilated place.

WARNINGS AND SAFETY INSTRUCTIONS

The paint is non-edible. The paint is not designated as a hazardous material and does not contain any materials requiring special marking or warning. Keep out of reach of children.

Specific information for this product can be found on the material safety data sheet (MSDS).

GENERAL COMMENTS

Do not paint when rain is expected in the next 72 hours and/or when temperatures are below 10°C and relative humidity is above 85%. When painting wood and metal infrastructures, make sure that the infrastructure being painted is completely dry. Never mix this material with materials not recommended by us. Achieving the desired results is subject to proper application of the product in strict conformance to our instructions. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted and their infrastructures have been properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

Synthetic paints' colors tend to change over time.

For further information feel free to call TELECOLOR - a free guidance calling line by Tambour: 1-800 -321-321

* Practical spreading rate can vary, depending on various causes: the surface, the application mode, the color, the painter's skill, and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** At 25°C and 65% relative humidity.

Manufactured by Tambour, certified ISO 9001 by the Standards Institution of Israel.