

Nirlat for the Bath

Washable mildew - preventing paint

Product Description

Acrylic paint for interior use, prevents the formation of mildew and fungi on walls. The paint is washable and "breathes" (is permeable to water vapor). Contains substances that inhibit the formation of mildew and fungi.

Typical Uses

Intended for painting interior walls prone to the formation of mildew and fungi, such as bathroom walls and floors, kitchens, public showers etc, where the humidity is high. Intended for walls where mildew has already appeared, or for new walls before the phenomenon is created.

Surface Preparation

On walls where mildew has already appeared, clean well to remove mildew with the aid of a hard plastic brush. Rinse the affected areas with household bleach, wait a few minutes and then, before it dries, rinse well with clean water to remove the bleach and mildew. Permit the surface to dry completely before painting. May be applied directly on existing paint, in 2-3 coats. On new plaster the surface should be sanded to remove grains of sand, and a coat of clear Primer S should be applied.

Application

Brush, roller or sprayer, until full and perfect surface coverage is obtained.

Clean Up

Tools can be cleaned with soap and water immediately after use.

General Remarks

Before application of the paint the wall must be cleaned to remove all traces of mildew and fungi.

Finish

Shade: White.
Gloss level: matte

Physical Properties

Contains: A water and mineral substance-based acrylic mixture & an anti-mildew and fungi substance.
Dilution: in water, 25% for the first coat, 10% for additional coats.
Coverage*: 5 m²/liter in two coats

The coverage capability is calculated according to the work of a skilled laborer on an infrastructure with an ordinary degree of absorption and may vary according to the working method, surface and weather conditions.

Limitations

Do not apply the material when the temperature is below 7°C or when rain is predicted.

Dry time

To recoat: 2-3 hours (under ordinary weather conditions)
To touch: 1 hours
Full cure: 72 hours

Shelf-life & Storage

12 months in a closed bucket, in a cool and dry place.

Packaging

1 liter and 5 liters

Health and Safety Precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with the eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat. **General Notes:** The aforementioned recommendations are not to be perceived as a substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty, either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.