

# Star Wash

## Product Description

Star Wash is a transparent water-based acrylic glaze with the addition of tiny crystals that create an attractive glittering effect. Star Wash is intended for application on interior walls and furniture. Gives interior walls a modern and unique look with an attractive glittering effect.

## Typical Uses

Suitable for application on existing walls painted with acrylic paint. New walls should be painted with Nirocryl 2000 or AC-100 acrylic paint as a background color. Achieve full coverage and allow the acrylic paint to dry completely before applying Star Wash. In general, it is advisable to apply **Cloud Wash** to acrylic paint before applying **Star Wash**. The maximal effect is obtained on a wall exposed to direct lighting.

## Application

Apply with a paintbrush using crisscross movements, once from the left and once from the right. Take a very small amount of Star Wash and spread it evenly on the surface. It is advisable to test the paint on a small area of the surface in order to determine the required quantity before applying to the entire wall.

## Clean Up

Tools can be cleaned with water immediately after use. Hands can be washed with soap and water immediately after application.

## Finish

**Shade:** transparent with silver, gold or Armageddon colored stars .

## Physical Properties

**Contains:** A water and polymeric pigment-based acrylic mixture.

**Dilution:** No need to dilute. The material is ready for application.

**Coverage\*:** 10 m<sup>2</sup> 0.5 l

The coverage capability is calculated according to the work of a skilled laborer on an infrastructure with an ordinary degree of absorption and may vary according to the working method, surface and weather conditions.

## Dry time

**To recoat:** Approximately 3 hours on top of the background coat (under ordinary weather conditions)

**Full cure:** 24 hours.

## Shelf-life & Storage

12 months in a cool and dry place and in its original closed packaging.

## Packaging

0.5 liter.

**Health and Safety Precautions:** The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with the eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat. **General Notes:** The aforementioned recommendations are not to be perceived as a substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty, either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.