

Material Safety Data Sheet

According to 91/155 EEC

Printing date 05.06.2005

Reviewed on 05.03.2010

1 Identification of the substance/preparation and of the company/undertaking

- Product details
- Trade name: TAMAGLASS SUPER MAT YELLOW EARTH PART A
- Article number: 393-051/Z equal to military article number 6670-14301
- Application of the substance / the preparation Polyurethan coating
- Manufacturer/Supplier: TAMBOUR LTD.
- Further information obtainable from: Health & Safety

2 Composition/information on ingredients

- Chemical characterization
- Description: Mixture of substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate	 Xi; R 10-36	25-50%
CAS: 1330-20-7 EINECS: 215-535-7	xylene (mix)	 Xn; R 10-20/21-38	10-25%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom.	 Xn; R 10-65	2.5-10%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate	R 10-66-67	2.5-10%
CAS: 108-94-1 EINECS: 203-631-1	cyclohexanone	 Xn; R 10-20	2.5-10%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene	 Xn,  F; R 11-20	1.0-2.5%

- Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- Hazard description:



Xn Harmful

- Information concerning particular hazards for human and environment:
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
R 10 Flammable.
R 20/21 Harmful by inhalation and in contact with skin.
R 36 Irritating to eyes.
- Classification system:
The classification is according to the latest editions of the EU-lists and extended by company and literature data.

Material Safety Data Sheet

According to 91/155 EEC

Printing date 05.06.2005

Reviewed on 05.03.2010

Trade name: TAMAGLASS SUPER MAT YELLOW EARTH PART A

(Contd. of page 1)

4 First aid measures

- General information:
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

- Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents:
Water
Water with full jet
- Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- Handling:
- Information for safe handling:
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.

- Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate

OES	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	New, IOELV, Sk

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 05.06.2005

Reviewed on 05.06.2010

Trade name: TAMAGLASS SUPER MAT YELLOW EARTH PART A

(Contd. of page 2)

1330-20-7 xylene (mix)	
OES	Short-term value: 662 mg/m ³ , 150 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
123-86-4 n-butyl acetate	
OES	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
108-94-1 cyclohexanone	
OES	Short-term value: 20 ppm Long-term value: 10 ppm New, IOELV, Sk
100-41-4 ethylbenzene	
OES	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm New, IOELV, Sk

- Additional information: The lists valid during the making were used as basis.
- Personal protective equipment:
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- Respiratory protection:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- General Information

Form: Fluid

(Contd. on page 4)

GB

Material Safety Data Sheet

According to 91/155 EEC

Printing date 05.06.2005

Reviewed on 05.03.2010

Trade name: TAMAGLASS SUPER MAT YELLOW EARTH PART A

(Contd. of page 3)

Colour:	According to product specification
Odour:	Characteristic
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	137°C
· Flash point:	21 - 55°C
· Ignition temperature:	315.0°C
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	10.8 Vol %
· Vapour pressure at 20°C:	6.7 hPa
· Density:	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Solvent content:	
Organic solvents:	34.7 %
Water:	0.0 %
VOC Content	34.7 %
· Solids content:	65.3 %

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided No decomposition if used according to specifications.
- Dangerous reactions No dangerous reactions known.
- Dangerous decomposition products No dangerous decomposition products known.

11 Toxicological information

- Acute toxicity:

· LD/LC50 values relevant for classification:		
1330-20-7 xylene (mix)		
Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful
Irritant

GB

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 05.06.2005

Reviewed on 05.03.2010

Trade name: TAMAGLASS SUPER MAT YELLOW EARTH PART A

(Contd. of page 4)

12 Ecological information

- General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- Product:
- Recommendation
Must not be disposed together with household waste. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- Land transport ADR/RID (cross-border)



- ADR/RID class: 3 Flammable liquids.
- Danger code (Kemler): 30
- UN-Number: 1263
- Packaging group: III
- Hazard label: 3
- Description of goods: 1263 PAINT (not viscous)

- Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1263
- Label: 3
- Packaging group: III
- EMS Number: F-E,S-E
- Marine pollutant: No
- Proper shipping name: PAINT

- Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1263
- Label: 3
- Packaging group: III
- Proper shipping name: PAINT

GB
(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 05.06.2005

Reviewed on 05.03.2010

Trade name: TAMAGLASS SUPER MAT YELLOW EARTH PART A

(Contd. of page 5)

15 Regulatory information

- Labelling according to EU guidelines:
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- Code letter and hazard designation of product:
Xn Harmful
- Hazard-determining components of labelling:
xylene (mix)
- Risk phrases:
 - 10 Flammable.
 - 20/21 Harmful by inhalation and in contact with skin.
 - 36 Irritating to eyes.
- Safety phrases:
 - 2 Keep out of the reach of children.
 - 23 Do not breathe gas/fumes/vapours/spray (appropriate wording to be specified by the manufacturer).
 - 36/37 Wear suitable protective clothing and gloves.
 - 46 If swallowed, seek medical advice immediately and show this container or label.
 - 51 Use only in well-ventilated areas.
 - 56 Dispose of this material and its container to hazardous or special waste collection point.
- National regulations:
- Technical instructions (air):

Class	Share in %
NK	65.4
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant R-phrases
 - 10 Flammable.
 - 11 Highly flammable.
 - 20 Harmful by inhalation.
 - 20/21 Harmful by inhalation and in contact with skin.
 - 36 Irritating to eyes.
 - 38 Irritating to skin.
 - 65 Harmful: may cause lung damage if swallowed.
 - 66 Repeated exposure may cause skin dryness or cracking.
 - 67 Vapours may cause drowsiness and dizziness.
- Department issuing MSDS: Tambour Ltd.- Health & Safety Department.
- Contact:
 - Haim Yahav
 - Phone: +972(4)987-7483
 - Fax: +972(4)985-3540
 - e-mail: h.yahav@tambour.co.il
- * Data compared to the previous version altered.

GB