

Marmarino

Product Description

Natural Marmarino is a decorative coating for interior use that creates an entire range of textures. Adding Wash on top of Marmarino creates a natural and special antiqued finish.

Typical Uses

Natural Marmarino is a particularly decorative product for interior wall finishes in apartments, hotels, offices, function halls and other places where an unusual wall finish is desired. Marmarino can be applied in various finishes that produce special effects by combining a varying coat depth and final finish in various shades of Wash.

Application

Can be applied on spackle plaster walls, gypsum walls and on top of old paint. Apply a complete first coat on the entire surface using a metal trowel. After initial drying of 10-20 minutes rub gently with a damp sponge. After the first coat is fully cured, a second coat can be applied in order to obtain the desired finish.

For a sandy finish: Apply a second complete coat on top of the first coat after it is partly dry. Rub gently with a sponge, using rotary motion, until a uniform appearance is obtained.

For a smoothed finish: After the first coat has cured fully, use a mortar or stainless steel trowel to apply a small amount of Marmarino, smoothing and compressing it using repeated rotary motions. Repeat the operation a second time around 10 minutes later, until the desired degree of smoothness is obtained.

Broken finish: Apply a first coat as above and, after it has cured fully, scatter patches of Marmarino on the surface and press with a stainless steel trowel in order to obtain a uniform texture of high areas and depressed areas on the entire surface. After the Marmarino has dried completely, at least 5-6 hours under ordinary conditions, Cloud Wash can be applied with the aid of a viscose sponge and distributed using a brush in a manner that highlights the texture of the Marmarino.

* Marmarino is applied in a quantity of 1.5-2.5 kg/m², according to the depth of the desired texture and the condition of the surface.

Clean Up

Tools can be washed with water immediately after use. Hands can be washed with soap and water immediately after application.

Finish

Shade: natural only

Finish: matte or satin, particularly smooth.

Physical Properties

Contains: A water-based acrylic mixture containing delicate aggregates.

Dilution: No need to dilute. The material is ready for application.

Coverage*: 1-2 kg/m².

The coverage capability is calculated according to the work of a skilled laborer on an infrastructure with an ordinary degree of absorption and may vary according to the working method, surface and weather conditions.

Dry time

To recoat: Approximately 3 hours for the first coat (under ordinary weather conditions)

Final drying: 24 hours.

Shelf-life & Storage

12 months in a cool and dry place and in its original closed packaging.

Packaging

7kg and 25 kg.

Health and Safety Precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with the eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat. **General Notes:** The aforementioned recommendations are not to be perceived as a substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty, either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.