

SAFARI

Coats series in a fine sand texture, lending a wild dune look to walls. For brush application in one coat, is various shades and/or metallic look on interior walls: **Pearleto** – semi-opaque pearl look; **Oro** – semi-opaque gold look; **Natural** – semi-opaque look in desert shades.

SPECIAL FEATURES:

Thick, water based, ready to use product.
Environment and user friendly.
Awarded the Green Label of the Israeli Standards Institute.

SUGGESTED USES:

Thick, water based paste, for easy and fast application on interior and exterior walls, painted with **acrylic paints** or **quartz primer**.

Technical Data:

	Safari Pearleto	Safari Oro	Safari Natural
Product Code	739-406	739-407	739-404
Color	Silvery pearl + 15 Tambourmix shades per shades chart	Gold + 6 shades in Tambourmix per shades chart	Basis for shades through the mix: 7 shades per shades chart
Gloss:	Satin	Satin	Matt-satin
Calculated spreading rate*: In one coat [sq.m/kg]	4.5-6	4.5-6	4-5
Thinner - Water Brush application	Ready to use – do not dilute	Ready to use – do not dilute	Ready to use – do not dilute

Recommended Thinner: **During Application:** Water **Cleaning:** Water
Drying Times: **Touch dry**:** 2 hours **Hard coat after brush application:** 24 hours
Shelf life: 24 months
Quantity per Pallet: **Package size** **Quantity per Pallet**

SURFACE PREPARATION AND PAINT SYSTEM:

Remove peeling and loose paint and dirt and dust residue off the wall. Apply broken white **Quartz primer** or the most similar shade to the chosen **Safari** shade.

PAINT APPLICATION:

To obtain the wild dune look on a smooth background:

Stir thoroughly before application and occasionally during application.

Dip a brush (3" – 4" wide) in the paint container.

Apply a small quantity of paste on the wall in wide crisscross movements (extending the full length of your arm). After covering a defined area, continue to 'play' in a free hand with the paste on the wall, applying it repeatedly, until islands of dune-like texture are created next to smooth areas (hills and ravines). It is recommended to apply over a diagonal section of about 0.5 sq./m at a time, and ensure complete coverage. It is recommended to step away from the wall occasionally during the application, to view the entire wall. If you wish to obtain a higher paste density, continue to load the brush and apply. Watch out for areas with excessive paste. If it tends to run, continue to spread the paste.

Use a dry brush to brush lightly in one direction, to obscure brush marks.

To obtain fabric-like texture:

Stir thoroughly before application and occasionally during application.

Dip a brush (3" – 4" wide) in the paint container. Apply crosswise, according to the following instructions:

- Apply the first coat over the entire width of the wall. Notch the paste across with a synthetic lawn head. Allow to dry to a hard coat.

Apply the second coat over the entire length of the wall. Notch vertically to the length of the coat with a synthetic lawn head.

Notes:

You may combine several shades together. To this purpose, allow to dry to a hard coat between the coats of the different shades.

Do not accelerate drying with a ventilator or a heat blower. To prevent splintering and cracks. The final shade and look is affected by the direct lighting on the wall and by the reflection of the room on the wall.

You may apply a second coat after the first coat dries to a hard coat (on the following day).

If you wish to revert to the smooth look in future, sand the wall and apply SUPERCRYL in the desired shade.

TOOLS CLEANING AND STORAGE:

Clean work tools with soap and water immediately upon completing the application. Pour a thin layer of water on the remaining product and close the container tightly to prevent air penetration. Store in a roofed, ventilated place.

CAUTION:

Inedible. The paste is not defined as a hazardous material and does not contain components requiring special marking or warning. Keep away from children. Provide adequate ventilation

of the work space during application.

Read the specific information for this product in the Safety Data Sheet (MSDS).

GENERAL COMMENTS:

Do not apply the paint when rain is expected and/or when ambient temperature falls below 10 degrees Celsius and relative humidity exceeds 85%. Do not mix this product with products that are not recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared.

Data presented here is based on our best knowledge and extensive experience. We reserve the right to update and/or alter it without prior notice.

* Practical spreading rate depends on several factors: The surface, the application mode, color shades, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** At 25°C and 65% relative humidity.

Produced by Tambour, authorized by the Israeli Institute of Standards, complying with ISO 9001.