

Wood Oil (Linseed)

For oiling and sealing wooden items. Turpentine based.

PROPERTIES

The oil penetrates the wood, fills in all the crevasses, provides it with flexibility and keeps it from drying. Preserves the wood's appearance and adds gloss. Suitable for the Israeli climate. Easy to apply. Suitable for all kinds of wood.

SUGGESTED USES

Protects exposed wood from drying and against dampness. For oiling and sealing wooden items. Can be used indoor or outdoor.

TECHNICAL DATA

Product code: 400- 585

Color: Transparent

Gloss: Silk

Calculated spreading rate (liter/m²): 10-20 m² / liter (single layer, depends on wood type and absorption)

Dilution: For painting: Ready to use **For cleaning:** Clean the brush with Tambour's mineral turpentine and then with soap and water

Drying times: 5 hours, **Hard dry**** : 48 hours **Time between layers:** 15 minutes (after absorbing the first layer, no need to wait for drying).

Shelf life: 24 months

Quantity for surface:	Container Size	Quantity for surface
	A quarter of American gallon	576
	American gallon	100

SURFACE PREPARATION AND PAINT SYSTEM

New unpainted wood:

For optimal absorption and bonding, polish the wood using a sandpaper to remove all the wood shells that are produced during smoothing and remove all of the polishing dust. Or - allow the wood to age for about 1-2 months so its porousness opens up. Paint any rough or scraped wood immediately when installing it.

Clean the surface of any dust, dirt and grease stains using **Varnit - cleaning agent** and wash thoroughly. The painting surface must be clean of any dirt, grease, wax and so on, so the wood absorption is maximal. Allow the wood to dry for 2-3 days.

Notes:

Do not paint over varnish.

We recommend that you check the penetration and absorption ability and color before using it, preferably in a hidden corner.

It is preferable to place wooden surfaces in at least a one degree grade, so water puddles are avoided.

APPLICATION REMARKS

The oil is ready to use. Stir well for the entire depth of the container prior to use and occasionally during application.

Paint a complete layer of **wood oil** using a brush or a roller. Paint one layer of the oil. After 15 minutes, after a complete absorption of the first layer is reached but before the first layer dries, apply a second layer ("wet on wet"). Remove leftovers, wipe out all the unabsorbed oil and wait for it to dry completely. Do not leave any paint "pools".

Wooden oil protects the wood by penetrating, allowing it a full protection and a rich appearance, and does not create any coating.

Maintenance:

When the oil begins to disappear, clean the wood using **Varnit - cleaning agent 585-200**. Wash with water thoroughly to remove any leftovers of the cleaning agent. Wait for it to dry completely and apply one layer of **wood oil** to freshen up the wood's appearance and to preserve its protection. No need to polish. It is recommended to renew at least every 3 months.

CLEANING AND STORAGE

Clean the tools with turpentine immediately after completing the work. Pour a thin layer of turpentine on any remaining paint and close container well so that it is airtight. Store in a dark, well-ventilated place.

WARNINGS AND SAFETY INSTRUCTIONS

This product is to be applied and used in accordance with safety, health and environmental quality in Israel. Users must read the warnings and safety instructions in the material safety data sheet (MSDS), which is available from Tambour's safety department. Tel: 04-9877483, and on the product label.

Keep away from fire and sparks. Non-edible. Make sure to provide adequate ventilation while working. Do not inhale fumes.

GENERAL COMMENTS

Do not paint when rain is expected in the next 72 hours and/or when temperatures are below 10°C and relative humidity is above 85%.

When painting wood and metal infrastructures, make sure that the infrastructure being painted is completely dry.

Keep out of reach of children.

Never mix this material with materials not recommended by us. Achieving the desired results is subject to proper application of the product in strict conformance to our instructions. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted and their infrastructures have been properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* Practical spreading rate can vary, depending on various causes: the surface, the application mode, the color, the painter's skill, and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** At 25°C and 65% relative humidity.

Manufactured by Tambour, certified ISO 9001 by the Standards Institution of Israel.

VARNIT – Decks Cleaning Agent

Decks exterior cleaning agent, designated to clean dirt and oil stains without affecting the fine texture of the wood and its look. Environment and user friendly.

Chlorine free. Does not affect vegetation. Concentrated and economical. Suitable for cleaning exterior wood, e.g., decks, beams, fences, pergolas, wooden furniture and more. Also suitable for interior wood cleaning and general cleaning of all types of surfaces: Including aluminum and copper surfaces, painted surfaces, plastic, glass, ceramics and other surfaces.

SPECIAL FEATURES:

- Environment friendly - quick biological decay.
- Based on natural sources.
- Disinfecting
- Effective and efficient
- Use as both concentrated and diluted solution.
- Pleasant fragrance.
- Non-toxic and non-flammable
- Safe for use
- Wide range applications

SUGGESTED USES:

To clean and refresh the deck, to prepare wood for painting and enhance the wood's appearance. Recommended for cleaning wooden surfaces outside the house, e.g., decks surrounding the house and the pool, garden furniture, roof frames, wooden fences and more.

TECHNICAL DATA:

Product Code: 585 -200

Color: Clear with a light orange shade

Calculated spreading rate*: About 50 sq.m/gallon (diluted with water at a 1:4 ratio)

Recommended Thinner: **For standard cleaning:** Dilute with water at a 1:4 ratio.

To Remove Sever Stains: Dilute with water at a 1:1 ratio.

Drying Times: Allow to act on wet wood for about 20 minutes and rinse with a water

jet. Allow to dry completely for 2-3 days prior to painting.

Shelf life: 24 months

Preparation:

- **Varnit Cleaning Agent** is environment friendly and does not affect plants or lawns.
- Remove any object that prevents contact of **Varnit Cleaning Agent** with the wood off the surface.
- Use a water hose to wet the entire surface thoroughly.
- You may mix **Varnit Cleaning Agent** with water at a ratio of up to 1 part cleaning agent with 4 parts of water.
- For extremely sever stains, you may mix **Varnit Cleaning Agent** with water at a ratio of 1:1.
- Do not add any bleach or any other material which is not recommended by Tambour.
- Mix only in containers made of plastic.
- It is recommended to construct the wood surface with a slope of one degree at least, to prevent water puddles.

Usage Directions:

- Apply the **Varnit Cleaning Agent** using a broom with hard bristles (not metal).
- Do not allow the surface to dry during the cleaning process.
- Allow the product to act for about 20 minutes, while maintaining a wet area.
- Use a water jet to rinse off all **Varnit Cleaning Agent** residue thoroughly.
- Allow the wooden surface to dry completely for 2-3 days prior to applying the top coat on the surface.
- It is recommended to clean surfaces in the morning or afternoon hours, to prevent accelerated drying of **Varnit Cleaning Agent**.
- General Maintenance and Cleaning: Clean periodically after paint application, to maintain a clean surface.

TOOLS CLEANING AND STORAGE:

Clean work tools with water immediately upon completing the application.

Store in a roofed, ventilated place.

CAUTION:

Any work that includes application and use of this product shall be performed according to the applicable Safety, Health and Environmental regulations in Israel. Read the the safety

precautions and the warnings specified in the Safety Data Sheet (MSDS), available at Tambour Safety Department, Telephone: 04-9877483 and indicated on the label of the product.

Keep away from fire and sparks. Inedible. Provide adequate ventilation of the work space. Do not inhale fumes.

GENERAL COMMENTS:

Keep away from children.

Do not mix this product with products that are not recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* Practical spreading rate depends on several factors: The surface, the application mode, color shades, the user's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

Produced by Tambour, authorized by the Israeli Institute of Standards, complying with ISO 9001.

VARNIT – Water Based Decks Varnish

Water based, polyurethane acrylic varnish for protecting deck surfaces and maintaining the natural texture of the wood.

SPECIAL FEATURES:

The varnish maintains the natural look of the wood, protects it from moisture penetration and contains an active anti-mold agent. The water based varnish dries quickly and is easily and conveniently applied. Lead and chromates free varnish. Environment friendly product, awarded a green label.

SUGGESTED USES:

The varnish is designated for protecting new or painted wood surfaces and maintains the natural texture of the wood. Indicated for application on wooden items in and outside the house, e.g., wooden decks, pergolas, wooden fences, tables, wooden furniture, doors, lintels, wooden toys, chairs, shelves and more.

TECHNICAL DATA:

Product Code:585-100

Color: Transparent + 11 wood shades for mixing in the Tambourmix machine

Gloss: Satin

Calculated spreading rate*: New unpainted wood: 9 sp.m/liter (in one coat)

Painted wood: 12 sq.m (in one coat)

Recommended Thinner: **During Application:** Water **Cleaning:** Water and soap

Drying Times: **Touch dry**:** 30 minutes; **Hard Coat:** 24 hours **Dry to recoat:** 2 hours

Shelf life: 24 months

Quantity per Pallet: **Package size**

Quantity per Pallet:

SURFACE PREPARATION AND PAINT SYSTEM:

New unpainted wood:

Sand the wood using sandpaper to remove the crust created by the plane, to allow optimal absorption and adhesion, then remove dust and grit. Or allow the wood to age slightly for 1-2 months and open its pores. For rough or scraped wood, apply the product immediately upon installation.

Clean all dust, dirt and oil stains off the surface with **Varnit Cleaning Agent** and rinse thoroughly. The surface must be clean of any dirt, oils, wax, etc., to ensure maximum absorption in the wood. Allow to dry for 2-3 days.

Painted Wood in Good Condition:

Sand lightly, clean with **Varnit Cleaning Agent** and apply the product according to the instructions.

Painted Wood in Poor Condition:

Sand thoroughly to remove paint residue, clean with **Varnit Cleaning Agent** and apply the product according to the instructions.

Notes:

A darker shade provides better protection. It is recommended to test porosity, absorption and shade prior to application, on a hidden corner. Catalog shades may be slightly different in practice, depending on the type of the painted wood. It is recommended to construct the wood surface with a slope of one degree at least, to prevent water puddles.

Do not apply on wet or moist wood.

Varnit Decks Varnish protects wood's interior by penetration and the wood's exterior by creating a protective coat.

PAINT APPLICATION:

Ready to use varnish. Stir the varnish thoroughly before application and occasionally during application. The transparent varnish has a whitish/ milky shade in the container, but once dry, it is transparent.

Application using a Varnish Brush/ Roller: Dilute the first coat with 30% water, to attain good absorption in the wood. Apply along the wood grain, until fully covered. Apply two additional coats without dilution (wait two hours between coats). Sand lightly with sandpaper No. 0 after each coat. Do not sand the last coat. Wipe paint residue off the wood.

Maintenance:

Surfaces exposed to extreme sunlight or heavy traffic may erode at a faster rate. In this case, clean the wood with **Varnit Cleaning Agent**. Rinse thoroughly with water to remove cleaning agent residue. Allow to dry and then apply one or two coats of **Varnit Deck Varnish** to refresh the appearance of the wood and maintain its protection. In the event of splitting or cracks, sand the surface and only then clean and apply the varnish. It is

recommended to renovate and refresh the deck once every six months at least.

TOOLS CLEANING AND STORAGE:

Clean work tools with soap and water immediately upon completing the application. Close the container tightly, to prevent air penetration.

Store in a roofed, ventilated place.

CAUTION:

Any work that includes application and use of this product shall be performed according to the applicable Safety, Health and Environmental regulations in Israel. Read the safety precautions and the warnings specified in the Safety Data Sheet (MSDS), available at Tambour Safety Department.

Telephone: 04-9877483 and indicated on the label of the product.

Keep away from fire and sparks. Inedible. Provide adequate ventilation of the work space.

Do not inhale fumes.

GENERAL COMMENTS:

Do not apply the paint when rain is expected within the next 72 hours and/or the deck is moist and/or when ambient temperature falls below 10 degrees Celsius and relative humidity exceeds 85%.

For application on wood and metal substrates, verify that the substrate is completely dry.

Keep away from children. Do not mix this product with products that are not recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* Practical spreading rate depends on several factors: The surface, the application mode, color shades, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** At 25°C and 65% relative humidity.

Green Label

Produced by Tambour, authorized by the Israeli Institute of Standards, complying with ISO 9001.

VARNIT DECK OIL WITH SPECIAL FORMULA

High quality deck oil with special formula for enhanced resistance to water penetration. A satin gloss clear oil that enables addition of a range of shades. Provides protection, fresh and decorative look to decks, wooden walls, furniture and wooden fences. Turpentine based.

SPECIAL FEATURES

Decks oil with exceptional clarity, maintains the look of the wood and adds gloss and bright color. Eases surface cleaning. Specifically adapted to the Israeli climate. High exterior resistance. Resists humidity and U.V. radiation. Contains an active anti-mold component. Very easy application. Suitable for all wood types.

SUGGESTED USES

Refresh decks, protect wood and enhance its look. Recommended for application on exterior wood surfaces, e.g., decks, around the house and the pool, garden furniture, casements, wooden fences and more.

TECHNICAL DATA

Product Code: 585-000 – clear base.

Color: Clear + 11 wood shading colors in Tambourmix system.

Gloss: Matt-satin.

Calculated spreading rate*: 10-20 sq.m/liter (in one coat depending on wood type and absorption)

Recommended Thinner During Application: Ready for use. **Cleaning:** Clean brush with Tambour Mineral Turpentine and then soap and water.

Drying Times: Touch dry**: 3-4 hours, **Hard coat:** 48 hours

Dry to recoat: 15 minutes (after the first coat is absorbed, do not wait for drying).

Shelf life: 24 months

Quantity per Pallet:	Package size	Quantity per Pallet:
	Quarter American Gallon	576
	American Gallon	100

SURFACE PREPARATION AND PAINT SYSTEM

New unpainted wood:

Sand the wood using sandpaper to remove the crust created by the plane, to allow optimal absorption and adhesion, then remove dust and grit. Or allow the wood to age slightly for 1-2 months and open its pores. For rough or scraped wood, apply the oil immediately upon installation.

Clean all dust, dirt and oil stains off the surface with **Varnit Cleaning Agent, Tambour Cat. No. 585-200** and rinse thoroughly. The surface must be clean of any dirt to ensure maximum absorption in the wood. Allow to dry for 2-3 days.

Notes:

A darker shade provides better protection. Do not apply over varnish. Completely remove all varnish first. ▪ It is recommended to test porosity, absorption and shade prior to application, on a hidden corner. Catalog shades may be slightly different in practice, depending on the type of the painted wood. It is recommended to construct the wood surface with a slope of one degree at least, to prevent water puddles.

PAINT APPLICATION:

Varnit Deck Oil is ready to use. Stir thoroughly before application right down to the bottom of the container and occasionally during application.

Apply a full coat of **Varnit Deck Oil** using a brush or a roller. Wait for 15 minutes after the first coat, and apply a second coat ("wet on wet") just before the first coat dries. Remove residue and wipe off any oil that was not fully absorbed by the wood. Allow to dry to a hard coat. **Varnit Deck Oil** protects the wood by penetration and provides protection and a rich look. It does not form a coat.

MAINTENANCE

Once the oil begins to disappear, clean the wood with **Varnit Cleaning Agent, Cat. No. 585-200** and rinse thoroughly to remove cleaning agent residue. Allow to dry. Apply one or two coats of **Varnit Deck Oil** to refresh the appearance of the wood and maintain its protection. Sanding is not required. It is recommended to renovate and refresh the deck once every six months at least.

TOOLS CLEANING AND STORAGE

Cleaning thinner: Turpentine. Clean tools with turpentine immediately after application is completed. Pour a thin layer of turpentine over the remaining oil and close the container tightly, to prevent air penetration. Store in a roofed, ventilated place.

CAUTION

Any work that includes application and use of this product shall be performed according to the applicable Safety, Health and Environmental regulations in Israel. Read the safety precautions and the warnings specified in the Safety Data Sheet (MSDS), available at Tambour Safety Department.

Telephone: 972-4-9877483 and indicated on the product's label. Keep away from fire and sparks. Inedible. Provide adequate ventilation of the work space. Do not inhale fumes when spraying.

GENERAL COMMENTS

Do not apply the paint when rain is expected within the next 72 hours and/or the deck is moist and/or when ambient temperature falls below 10 degrees Celsius and relative humidity exceeds 85%. For application on wood and metal substrates, verify that the substrate is completely dry. Never mix this material with others when not specifically recommended by us. The desired results are obtained only through correct application of the product according to the application instructions. The user must ensure, prior to application, that the products are designated for the intended use thereof and that the surface and substrate to be painted were properly prepared and are suitable for product application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

- * Practical spreading rate depends on several factors: The surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.
- ** At 25°C and 65% relative humidity.