

Veneziano Stucco Plaster

Product Description

Veneziano is a special paste that gives interior walls in buildings the appearance of smooth natural marble with a satin finish, in a wide range of colors and a unique effect. A Veneziano finish gives interior walls a splendid and noble appearance that can be obtained only with this product. The wall won't pick up dirt and will retain its special appearance over time.

Typical Uses

Can be applied to new walls after they have been smoothed with two coats of Gold Bond American putty or on existing walls after suitable preparation. Also suitable for application on gypsum walls and on gypsum plaster walls.

Application

New walls – after sanding and smoothing with two coats of Gold Bond American putty. In the case of gypsum walls, one coat of putty is generally sufficient. Can also be applied on gypsum plaster. Clean the surface after rubbing to remove sanding dust and apply Bonding Primer for Colored in a shade similar to the required shade of Veneziano, or an undercoat of clear Primer S. Veneziano is applied with the aid of a stainless steel trowel in a thin coat. Apply the first coat using a rotary motion. Do not apply in straight lines. Apply to the entire wall and leave to dry for at least 4 hours before applying the second coat. For the second coat apply a thin coat with the aid of a mortar using semicircular movements, like a figure S, first in one direction and then in the opposite direction. While applying the material smooth it with the mortar using rapid movements. The width of the mortar will determine the nature of the pattern that is obtained, to a great extent. Continue smoothing the surface during the drying process of the Veneziano. The gloss level that is obtained depends on the extent to which the paint is pressed and smoothed while drying. PLC can be applied on top of the Veneziano one day after application, in order to enhance the walls' resistance to water and dirt.

Clean Up

Tools and hands can be cleaned with soap and water immediately after use.

Finishing

Shade: According to the shades in the Stucco Veneziano catalogue.

Finish: Especially smooth, available in various gloss levels.

Physical Properties

Contains: especially delicate water-based acrylic paste.

Dilution: No need to dilute. The material is ready for application.

Coverage*: 1 kg per 2-2.5 square meter.

The coverage capability is calculated according to the work of a skilled laborer on an infrastructure with an ordinary degree of absorption and may vary according to the working method, surface and weather conditions.

Limitations

Do not apply the material when the temperature is below 5°C or above 35°C.
For interior walls only.

Dry time

Between coats: Approximately 3 hours for the first coat (under ordinary weather conditions)

Final drying: 24 hours.

Shelf-life & Storage

12 months in a cool and dry place and in its original closed packaging.

Packaging

7 kg and 25 kg bucket
(After coloring is added, the weight increases according to the color)

Health and Safety Precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with the eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat. **General Notes:** The aforementioned recommendations are not to be perceived as a substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty, either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.